
FLARE



STRIP LIGHT W Κ Lumen L/W CRI FL2835.180.14.27.8 2700K 1580 109.7 ≥80 FL2835.180.14.3.8 3000K 1610 111.8 ≥80 14.4 FL2835.180.14.4.8 4000K 1630 113.2 ≥80 FL2835.180.14.5.8 5000K 1630 113.2 ≥80 FL2835.180.14.27.9 2700K 1350 93.8 ≥90 FL2835.180.14.3.9 3000K 1370 95.1 ≥90 14.4 FL2835.180.14.4.9 4000K ≥90 1390 96.5 FL2835.180.14.5.9 5000K 1390 96.5 ≥90

SMD	24V	IP20	50,000h
DALI	1/10V	PUSH	120°

Technical Specifications:

I ED	flexible	ctrip	liabt
ヒヒレ	Tiexible	STrid	light

IP Rating: 20

Material: made of high quality FPC board

Flexible white circuit which comes in 10mm width to apply more heat release. The product is supplied in 5 meter coils

Supplied with connection cable on both sides for connections in line or power supply

The back of the circuit is provided with adhesive tape for quick application

Number of leds: 180

Voltage: 24V DC

LED Type: SMD

CRI: >80 & 90

Mini. Segment: 33.3mm

LED Pitch: 5.55mm

