

FLARE



COB	48V	IP20	50,000h
DALI	I/10V	PUSH	16/24/36°

Tec. Specifications:

Cylindrical round adjustable track spotlight for track system

Material: Made of aluminum alloy, the adapter made of poly carbonate

Connection: With adapter used for track rail three-phase

LED Type: COB

CRI: ≥90

UGR: ≤19

Driver: Fits on the housing of the adapter easy connectivity of the adapter electrically and mechanically to the track

Dimming: Option to apply DALI / I-10 V / trailing edge dimmable driver

IP Rating: 20

Dimming Option:

DALI	D
I-10V	V
Push	P

Body Finish:

Black B

Reflector Finish:

Glossy White
Glossy Black
Specular

Beam Angle:

16	1
24	2
36	3

Dimensions:

Watt	W	H
6	38.5	103.4
9	50	114
12	60	124

KET-T

	W	K	Lumen	L/W	CRI
FL0302.6.3	6	3000K	388	64.6	≥90
FL0302.6.4		4000K	427	71.2	≥90
FL0302.9.3	9	3000K	595	66.1	≥90
FL0302.9.4		4000K	655	72.8	≥90
FL0302.12.3	12	3000K	998	83.1	≥90
FL0302.12.4		4000K	1088	90.6	≥90

