

# FLARE



|           |     |      |         |
|-----------|-----|------|---------|
| COB       | 48V | IP20 | 50,000h |
| 15/24/36° |     |      |         |

**Tec. Specifications:**

Cylindrical round adjustable track spotlight for track system

**Material:** Made of aluminum alloy, the adapter made of poly carbonate

**Connection:** With adapter used for track rail three-phase

**LED Type:** COB

**CRI:** ≥90

**UGR:** ≤19

**Driver:** Fits on the housing of the adapter  
easy connectivity of the adapter electrically and mechanically to the track

**IP Rating:** 20

**Body Finish:**

Black B

White W

**Reflector Finish:**

Black B

White W

**Beam Angle:**

15 1

24 2

36 3

**Dimensions:**

Watt H W

7 90 35

12 100 45

20 140 65

**M30-T**

|             | W  | K     | Lumen | CRI |
|-------------|----|-------|-------|-----|
| FL365.7.27  | 7  | 2700K | 420   | ≥90 |
| FL365.7.3   |    | 3000K | 455   | ≥90 |
| FL365.7.4   |    | 4000K | 490   | ≥90 |
| FL365.12.27 | 12 | 2700K | 720   | ≥90 |
| FL365.12.3  |    | 3000K | 780   | ≥90 |
| FL365.12.4  |    | 4000K | 840   | ≥90 |
| FL365.20.27 | 20 | 2700K | 1200  | ≥90 |
| FL365.20.3  |    | 3000K | 1300  | ≥90 |
| FL365.20.4  |    | 4000K | 1400  | ≥90 |

