

FLARE



COB	230V	IP20	50,000h
DALI	I/I0V	PUSH	90°

Technical Specifications:

Recessed round luminaire

Material: Body made of die-cast aluminum and passive dissipation system

Reflector: PC white reflector Insuring lighting efficiency and anti-glare light

LED Type: SMD

CRI: >80

UGR: <19

Diffuser: Opal diffuser

Driver: Remote driver

Dimming: Option to apply DALI / I-10 V / trailing edge dimmable driver

IP Rating: 20

Dimming Option:

DALI	D
I-10V	V
Push	P

Dimensions / * Cutout

Watt	W	H	D *
10	105	65	85
15	130	68	105
20	165	90	140
30	185	95	165
40	220	105	200

Wago

	W	K	Lumen	L/W	CRI
FL0220.10.3	10	3000K	868	86.8	≥80
FL0220.10.4		4000K	911	91.1	≥80
FL0220.15.3	15	3000K	1345	89.6	≥80
FL0220.15.4		4000K	1412	94	≥80
FL0220.20.3	20	3000K	1928	96.4	≥80
FL0220.20.4		4000K	2024	101	≥80
FL0220.30.3	30	3000K	2679	89.3	≥80
FL0220.30.4		4000K	2820	94	≥80
FL0220.40.3	40	3000K	3554	88.8	≥80
FL0220.40.4		4000K	3731	93.2	≥80

