

# FLARE



|      |     |      |         |
|------|-----|------|---------|
| SMD  | 48V | IP20 | 50,000h |
| 110° |     |      |         |

**Technical Specifications:**

Recessed rectangular modular mini linear light for the linear system

**Matirial:** Made of extruded aluminum

**Diffuser:** PMMA opal diffuser

**LED Type:** SMD

**CRI:** ≥90

**UGR:** ≤19

**Driver:** Fits on the housing of the module

Easy connectivity of the adapter electrically and mechanically to the track

**IP Rating:** 20

**Finishes:**

Black    B

White    W

**Dimension:**

|      |      |    |    |
|------|------|----|----|
| Watt | L    | W  | H  |
| 12   | 300  | 22 | 25 |
| 20   | 600  | 22 | 25 |
| 30   | 900  | 22 | 25 |
| 40   | 1200 | 22 | 25 |

**M30-L**

|             | W  | K     | Lumen | CRI |
|-------------|----|-------|-------|-----|
| FL362.12.27 | 12 | 2700K | 552   | ≥90 |
| FL362.12.3  |    | 3000K | 600   | ≥90 |
| FL362.12.4  |    | 4000K | 660   | ≥90 |
| FL362.20.27 | 20 | 2700K | 940   | ≥90 |
| FL362.20.3  |    | 3000K | 1000  | ≥90 |
| FL362.20.4  |    | 4000K | 1100  | ≥90 |
| FL362.30.27 | 30 | 2700K | 1410  | ≥90 |
| FL362.30.3  |    | 3000K | 1500  | ≥90 |
| FL362.30.4  |    | 4000K | 1650  | ≥90 |
| FL362.40.27 | 40 | 2700K | 1880  | ≥90 |
| FL362.40.3  |    | 3000K | 2000  | ≥90 |
| FL362.40.4  |    | 4000K | 2200  | ≥90 |

