

# FLARE



|      |       |      |           |
|------|-------|------|-----------|
| SMD  | 230V  | IP20 | 50,000h   |
| DALI | I/I0V | PUSH | 15/30/45° |

## Technical Specifications:

Recessed rectangular modular mini spot light

**Material:** made of extruded aluminum

Number of optics: 1, 2, 5 & 10 fix optics

**Reflector:** PC black anti-glare screen

Surface trim colors are available for customer's preference in black & white

**LED Type:** SMD

**CRI:** ≥90

**UGR:** <19

**Diffuser:** Clear diffuser

**Driver:** Remote driver

**Dimming:** Option to apply DALI / 1-10 V / trailing edge dimmable driver

**IP Rating:** 20

### Dimming Option:

|       |   |
|-------|---|
| DALI  | D |
| 1-10V | V |
| Push  | P |

### Frame Finish:

|       |   |
|-------|---|
| Black | B |
| White | W |

### Beam Angle:

|    |   |
|----|---|
| 15 | 1 |
| 30 | 2 |
| 40 | 3 |

### Dimensions / \* Cutout

| Watt | W      | H  | D *    |
|------|--------|----|--------|
| 2    | 45*45  | 49 | 37*37  |
| 4    | 75*45  | 49 | 68*37  |
| 10   | 147*45 | 49 | 140*37 |
| 20   | 280*45 | 49 | 273*37 |

## RUTH

|             | W  | K     | Lumen | L/W   | CRI |
|-------------|----|-------|-------|-------|-----|
| FL0409.2.3  | 2  | 3000K | 210   | 105   | ≥80 |
| FL0409.2.4  |    | 4000K | 220   | 110   | ≥80 |
| FL0409.4.3  | 4  | 3000K | 444   | 111   | ≥80 |
| FL0409.4.4  |    | 4000K | 523   | 130   | ≥80 |
| FL0409.10.3 | 10 | 3000K | 898   | 89.8  | ≥80 |
| FL0409.10.4 |    | 4000K | 1057  | 105.7 | ≥80 |
| FL0409.20.3 | 20 | 3000K | 1480  | 74    | ≥80 |
| FL0409.20.4 |    | 4000K | 1741  | 87    | ≥80 |

