

FLARE



SMD	230V	IP20	50,000h
DALI	I/I0V	PUSH	15/30/45°

Technical Specifications:

Recessed rectangular trimless modular mini spot

Material: made of extruded aluminum

Number of optics: 1, 2, 5 & 10 fix optics

Reflector: PC black anti-glare screen

Surface trim colors are available for customer's preference in black & white

LED Type: SMD

CRI: ≥90

UGR: <19

Diffuser: Clear diffuser

Driver: Remote driver

Dimming: Option to apply DALI / 1-10 V / trailing edge dimmable driver

IP Rating: 20

Dimming Option:

DALI	D
1-10V	V
Push	P

Finish:

Black	B
White	W

Beam Angle:

15	1
30	2
45	3

Dimensions / * Cutou

Watt	W	H	D *
2	41*72	49	42*41
4	71*72	49	72*41
10	143*72	49	145*41
20	276*72	49	277*41

RUTH-T

	W	K	Lumen	L/W	CRI
FL0410.2.3	2	3000K	210	105	≥80
FL0410.2.4		4000K	220	110	≥80
FL0410.4.3	4	3000K	444	111	≥80
FL0410.4.4		4000K	523	130	≥80
FL0410.10.3	10	3000K	898	89.8	≥80
FL0410.10.4		4000K	1057	105.7	≥80
FL0410.20.3	20	3000K	1480	74	≥80
FL0410.20.4		4000K	1741	87	≥80

