

FLARE



SMD	230V	IP20	50,000h
DALI	I/10V	PUSH	15/30/45°

Technical Specifications:

Direct light modular system with LED lamps

Material: The structure is made of extruded aluminum, with end caps on both sides

Can be used in different dimensions or as a continuous line

Fixing Type: Luminaire can be surface mounted or suspended with suspension kit

Optics: 2 or more groups of 5 rectangular modular mini

LED Type: SMD

CRI: >80

UGR: <19

Driver: Integrated driver in the luminaire

Dimming: Option to apply DALI / I-10 V / trailing edge dimmable driver

IP Rating: 20

Dimming Option:

DALI	D
I-10V	V
Push	P

Beam Angle:

1	15
2	30
3	45

Finish:

Black	B
White	W

Dimensions:

Watt	L	W	H
10	570	35	80
20	1130	35	80
30	1410	35	80
30	1690	35	80
40	2250	35	80

SEON-S

	W	K	Lumen	L/W	CRI
FL0336-10-3	10	3000K	947	94.7	≥80
FL0336-10-4		4000K	957	95.7	≥80
FL0336-20-3	20	3000K	1651	82.5	≥80
FL0336-20-4		4000K	1705	85.2	≥80
FL0336-30-3	30	3000K	2295	76.5	≥80
FL0336-30-4		4000K	2323	77.4	≥80
FL0336-1-30-3	30	3000K	2460	82	≥80
FL0336-1-30-4		4000K	2629	87.6	≥80
FL0336-40-3	40	3000K	3320	83	≥80
FL0336-40-4		4000K	3520	88	≥80

