FLARE



	W	К	Lumen	L/W	CRI
FL2835.240.24.27.8		2700K	2590	107.9	≥80
FL2835.240.24.3.8	24	3000K	2640	111.8	≥80
FL2835.240.24.4.8	24	4000K	2760	113.2	≥80
FL2835.240.24.5.8		5000K	2760	113.2	≥80
FL2835.240.24.27.9		2700K	2200	93.8	≥90
FL2835.240.24.3.9	24	3000K	2240	95.I	≥90
FL2835.240.24.4.9	24	4000K	2340	96.5	≥90
FL2835.240.24.5.9		5000K	2340	96.5	≥90

SMD	24V	IP20	50,000h
DALI	1/10V	PUSH	120°

Technical Specifications:

LED flexible strip light
Material: Made of high quality FPC board
Flexible white circuit which comes in 10mm width to
apply more heat release. The product is supplied in 5
meter coils
Supplied with connection cable on both sides for
connections in line or power supply
The back of the circuit is provided with adhesive tape
for quick application
Number of leds/meter: 240
Number of leds/meter: 240
Number of leds/meter: 240 Voltage: 24V DC
Number of leds/meter: 240 Voltage: 24V DC LED Type: SMD
Number of leds/meter: 240 Voltage: 24V DC LED Type: SMD CRI: >80 & 90
Number of leds/meter: 240 Voltage: 24V DC LED Type: SMD CRI: >80 & 90 Mini. Segment: 25mm

