



STRIP LIGHT

|                    | W  | K     | Lumen | L/W   | CRI |
|--------------------|----|-------|-------|-------|-----|
| FL2835.140.28.27.8 | 28 | 2700K | 2910  | 103.9 | ≥80 |
| FL2835.140.28.3.8  |    | 3000K | 2980  | 106.4 | ≥80 |
| FL2835.140.28.4.8  |    | 4000K | 3090  | 110.4 | ≥80 |
| FL2835.140.28.5.8  |    | 5000K | 3090  | 110.4 | ≥80 |
| FL2835.140.28.27.9 | 28 | 2700K | 2470  | 88.2  | ≥90 |
| FL2835.140.28.3.9  |    | 3000K | 2530  | 90.4  | ≥90 |
| FL2835.140.28.4.9  |    | 4000K | 2630  | 93.9  | ≥90 |
| FL2835.140.28.5.9  |    | 5000K | 2630  | 93.9  | ≥90 |

|      |       |      |         |
|------|-------|------|---------|
| SMD  | 24V   | IP20 | 50,000h |
| DALI | 1/10V | PUSH | 120°    |

Technical Specifications:

LED flexible strip light

**Material:** Made of high quality FPC board

Flexible white circuit which comes in 15mm width to apply more heat release. The product is supplied in 5 meter coils

Supplied with connection cable on both sides for connections in line or power supply

The back of the circuit is provided with adhesive tape for quick application

**Number of leds/meter:** 140

**Voltage:** 24V DC

**LED Type:** SMD

**CRI:** >80 & 90

**Mini. Segment:** 83.33mm

**LED Pitch:** 13.89mm

**IP Rating:** 20

