

# FLARE



|      |       |      |           |
|------|-------|------|-----------|
| COB  | 230V  | IP20 | 50,000h   |
| DALI | I/10V | PUSH | 15/24/36° |

## Technical Specifications:

Cylindrical round adjustable track spotlight

**Material:** Made of aluminum alloy, the adapter made of poly carbonate

**Connection:** With adapter used for track rail three-phase

**LED Type:** COB

**CRI:** ≥80

**UGR:** ≤19

**Driver:** Fits on the housing of the adapter.

Easy connectivity of the adapter electrically and mechanically to the track

**Dimming:** Option to apply DALI / I-10 V / trailing edge dimmable driver

**IP Rating:** 20

## Dimming Option:

|       |   |
|-------|---|
| DALI  | D |
| I-10V | V |
| Push  | P |

## Reflector+ Body Finish:

|       |   |
|-------|---|
| White | W |
| Black | B |

## Beam Angle:

|    |   |
|----|---|
| 15 | 1 |
| 24 | 2 |
| 36 | 3 |

## Dimensions:

| Watt | H  | L   |
|------|----|-----|
| 10   | 50 | 163 |
| 20   | 60 | 163 |
| 30   | 80 | 170 |
| 40   | 90 | 185 |

## FEBE

|             | W  | K     | Lumen | L/W   | CRI |
|-------------|----|-------|-------|-------|-----|
| FL0502.10.3 | 10 | 3000K | 806   | 80.6  | ≥80 |
| FL0502.10.4 |    | 4000K | 1217  | 121.7 | ≥80 |
| FL0502.20.3 | 20 | 3000K | 2015  | 100.7 | ≥80 |
| FL0502.20.4 |    | 4000K | 2212  | 110.6 | ≥80 |
| FL0502.30.3 | 30 | 3000K | 2779  | 92.6  | ≥80 |
| FL0502.30.4 |    | 4000K | 3600  | 120   | ≥80 |
| FL0502.40.3 | 40 | 3000K | 4035  | 100.8 | ≥80 |
| FL0502.40.4 |    | 4000K | 4657  | 116   | ≥80 |

